XD700U

Mobile projection with bright, vivid images.

XGA | DLP | 5000 | 3000:1 | 28 dBA | 4.1 kg

Brilliant-Color™ | Color Enhancer | Wall Screen | User Logo Projection | 10 W Speaker | Instant Shut Down | Long Life Lamp | LAN Control | HDMI | Audio Mix Function | Computer-free Presentation | Efficient Mode

Picture Performance | Presentation | User/environmentally friendly

Specifications

Technology	0.7" 1-Chip DMD, 12° LVDS, DDP2431
Resolution	1024 x 768 (total 786,432 pixels)
Brightness	5000 ANSI lumens
Contrast	3000:1 (on/off)
Vertical Frequency (V-Sync)	50–120 Hz
Horizontal Frequency (H-Sync)	15–105 kHz
Band Width	up to 165 MHz
Projector Lamp	230 W
Lamp Life	approx. 5000 hours (low mode)[1]
Lens	F = 2.4–2.8, f = 20.6–30.1 mm
Focus/Zoom	Manual focus and zoom (zoom ratio: 1.5:1)
Throw Ratio	1.44–2.1:1
Picture Diagonal	1.02–7.62 m
Fan Noise	28 dB (low mode)
Audio Speaker	10 W mono
PC Compatibility	640 x 480 to 1024 x 768 pixels (compr. 1600 x 1200 pixels), incl. Composite Sync, sync on green available
Video Compatibility	NTSC/NTSC 4.43, PAL (incl. PAL-M, N), SECAM, PAL-60, Comp. Video: 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i/p (1125i/p 60Hz), 1080i/p (1125i/p 50Hz)
Features	Lens Shift (vertical), automatic Keystone Correction, 5-Segment Color Wheel (R/G/B/W/Y), USB Display, LAN Display (incl. remote desktop), PTG function, JPEG Viewer, Creston/AMX Compatibility, PJ Link available, 3D Ready, Visual PA, Stand-by Audio, Audio Mix Function, Easy Lamp Access, Instant Shut Down, Efficient Mode

Input Terminals	RGB: 2 x mini-D-sub 15-pin Audio: 2x stereo-mini-jack (Ø 3.5 mm) Video: RCA, S-VIDEO Digital: HDMI Video Audio: RCA (L/R)
Output Terminals	RGB: mini-D-sub 15-pin Audio: stereo-mini-jack (Ø 3.5 mm)
Communication Terminals	RS232C, D-sub 9-pin, LAN (RJ-45), USB Type A, USB Type B
Remote Control	Projector fully control
Dimensions (W x H x D)	345 x 134 x 270 mm (not included protrusion)
Weight	4.1 kg
Power Consumption	max. 405 W, approx. 0.5 W stand-by
Power Supply	AC 100–240 V, 50/60 Hz
Supplied Accessories	Softbag, Remote Control (incl. batteries), Cable Set, Multilingual User Manual (CD-ROM), Quick Start Guide, Safety Manual, Lamp Replacement Attachment, Lens Cap
Optional Accessories	Optional lamp (VLT-XD700LP)

[1]Depending on the operation environment and application. This is an average value given by the manufacturer based on ideal conditions.

eco Changes for a greener tomorrow

Eco Changes is the Mitsubishi Electric Group's environmental statement, and expresses the Group's stance on environmental management. Through a wide range of businesses, we are helping contribute to the realization of a sustainable society.

Mitsubishi Electric Europe B.V. • German Office • Visual Information Systems
Gothaer Strasse 8 • D-40880 Ratingen
Tel.: +49 (0) 21 02/4 86 92 50 • Fax: +49 (0) 21 02/4 86 68 40 • **www.Mitsubishi-VIS.de**

MITSUBISHI ELECTRIC
Changes for the Better

The right to make technical changes is reserved; no liability is accepted for printing or other errors.